

## XT-Compressible tape



### Technical specification

<b>Material</b>	Open cell polyurethane foam impregnated with acrylic based UV stabilised resin.
<b>Widths</b>	20 and 25mmmm
<b>Roll lengths</b>	8m or 4.3 m
<b>Gap size to seal</b>	3-7mm or 7-12mm

### Performance information

<b>Building classification (DIN 4102)</b>	B1, self extinguishing, P-NDS 04-229
<b>Exposure class for impregnated foam tapes</b>	<b>(DIN 18542)</b> – BG1
<b>Thermal conductivity (DIN 52612)</b>	$\lambda_{10} < 0.48 \text{ W / m/K}$
<b>Vapour resistivity (DIN 52615)</b>	$\mu < 100$
<b>Resistance to root penetration (DIN 4062)</b>	The requirements of DIN standard are met.
<b>Air permeability (DIN 18542)</b>	$\alpha < 1.0 \text{ m}^3 / [\text{h.m}(\text{daPa})^{2/3}]$
<b>Weather tightness against driving rain (DIN18542 / EN1027)</b>	Minimum 600Pa
<b>Compatability with building products</b>	No adverse effects with iron, Zinc, steel, galvanised steel, aluminium, concrete, stone, PVC, timber

## **XT-Compressible tape**

### **Technical specification**

<b>Life expectancy</b>	> 25 years
<b>Performance guarantee</b>	15 years warranty on performance
<b>Service temperature</b>	-30°C to + 90°C
<b>Storage</b>	Store horizontally in cartons +1°C - 25°C in dry conditions away from direct sunlight.
<b>Shelf life</b>	2 years when stored in original unopened boxes